



HAFEZ GROUP
Environmental Solutions

**COMPANY
PROFILE**



Find us on



Scan me

ABOUT US

01



MISSION & VISION





Vision

Make the world safer to live in.

Mission

To be the leader in Mena region for providing sustainable solutions and the highest quality of recycled plastic raw materials to make customers satisfied Via satisfied employees





OUR VALUES

03



Our Values

INTEGRITY: We act with respect, honesty, and transparency.

ACCOUNTABILITY: We have high standards and take pride in our work.

INNOVATION: We encourage cut edge ideas, and improvements.

EXCELLENCE: We do what we say and communicate any changes.

BUILD RELATIONS: We bring together stakeholders and maximize value.





WHAT WE DO

04

What we Do ?

Environmental solutions to assist organizations and individuals towards brighter future

1-Waste management :

- Collecting
- Sorting
- Transporting
- Recycling
- Providing plastic recycled pellets
- Giving testimony of waste management

2- Doing industrial recycling to produce high quality recycled plastic pellets :


- LLDPE recycled plastic pellets
- LDPE recycled plastic pellets
- HDPE recycled plastic pellets
- PP recycled plastic pellets



As we provide customized sort of plastic recycled pellets and customized services that matches your requirement


Find us on




+20 1040040 199 

Abo almanga ,Slow Road ,Basos ,El Qanater El Khayreya ,Qalyubia ,Egypt 

+20 1050051555 

+20 1111 6200 67 

info@hafezgroup.org 

+20 111 0909436 

www.hafezgroup.org 

SOME OF OUR PRODUCTS

05

HF-LDNATURAL



TECHNICAL DATA SHEET

Recycled Low Density Polyethylene (LDPE)
rLDPE [CASRN 9002-88-4]

PRODUCT TECHNICAL PROPERTIES

Properties	Value	Unit	Testing Conditions	Test Method
Density	0.932 ± 0.03	g/cm ³	23 °C	ASTM D-792
Melt Flow Index	0.93 ± 0.3	g/10 min	190°C - 2.16 kg	ASTM D-1238
Ultimate Tensile Stress	≥ 15.5	MPa	50 mm/min	ASTM D-638
Elongation at Break	≥ 1000	%	50 mm/min	ASTM D-638
Ash Content	≤ 0.2	%	60 min. - 700 °C	ASTM D-5630
Moisture Content	≤ 0.1	%	60 min. - 100 °C	ASTM D-6980

Recommended Application

This recycled Polyethylene grade is suitable for Polyethylene applications such as film, sheet, shopping bag, irrigation tube and electrical hose.etc..

PACKAGING

The default Package is 25 kg pack .
We could customize the package upon your request.



HF-LDHONEY



TECHNICAL DATA SHEET

Recycled Low Density Polyethylene (LDPE)
rLDPE [CASRN 9002-88-4]

PRODUCT TECHNICAL PROPERTIES

Properties	Value	Unit	Testing Conditions	Test Method
Density	0.925 ± 0.03	g/cm ³	23 °C	ASTM D-792
Melt Flow Index	0.5 ± 0.3	g/10 min	190°C - 2.16 kg	ASTM D-1238
Ultimate Tensile Stress	≥ 16.5	MPa	50 mm/min	ASTM D-638
Elongation at Break	≥ 950	%	50 mm/min	ASTM D-638
Ash Content	≤ 0.2	%	60 min. - 700 °C	ASTM D-5630
Moisture Content	≤ 0.1	%	60 min. - 100 °C	ASTM D-6980

Recommended Application

This recycled Polyethylene grade is suitable for Polyethylene applications such as film, sheet, shopping bag, irrigation tube and electrical hose.etc..

PACKAGING

The default Package is 25 kg pack .
We could customize the package upon your request.



HF-LDCOLOR



TECHNICAL DATA SHEET

Recycled Low Density Polyethylene (LDPE)
rLDPE [CASRN 9002-88-4]

PRODUCT TECHNICAL PROPERTIES

Properties	Value	Unit	Testing Conditions	Test Method
Density	0.990 ± 0.03	g/cm ³	23 °C	ASTM D-792
Melt Flow Index	0.6 ± 0.3	g/10 min	190°C - 2.16 kg	ASTM D-1238
Ultimate Tensile Stress	≥ 18	MPa	50 mm/min	ASTM D-638
Elongation at Break	≥ 900	%	50 mm/min	ASTM D-638
Ash Content	≤ 0.3	%	60 min. - 700 °C	ASTM D-5630
Moisture Content	≤ 0.1	%	60 min. - 100 °C	ASTM D-6980

Recommended Application

This recycled Polyethylene grade is suitable for Polyethylene applications such as film, sheet, shopping bag, irrigation tube and electrical hose.etc..

PACKAGING

The default Package is 25 kg pack .
We could customize the package upon your request.



HF-LDBLACK

TECHNICAL DATA SHEET

Recycled Low Density Polyethylene (LDPE)
rLDPE [CASRN 9002-88-4]



PRODUCT TECHNICAL PROPERTIES

Properties	Value	Unit	Testing Conditions	Test Method
Density	0.990 ± 0.03	g/cm ³	23 °C	ASTM D-792
Melt Flow Index	0.6 ± 0.3	g/10 min	190°C - 2.16 kg	ASTM D-1238
Ultimate Tensile Stress	≥ 18	MPa	50 mm/min	ASTM D-638
Elongation at Break	≥ 900	%	50 mm/min	ASTM D-638
Ash Content	≤ 0.5	%	60 min. - 700 °C	ASTM D-5630
Moisture Content	≤ 0.1	%	60 min. - 100 °C	ASTM D-6980

Recommended Application

This recycled Polyethylene grade is suitable for Polyethylene applications such as film, sheet, shopping bag, irrigation tube and electrical hose.etc..

PACKAGING

The default Package is 25 kg pack .
We could customize the package upon your request.



LDPE BLACK

TECHNICAL DATA SHEET

Recycled Low Density Polyethylene (LDPE)
rLDPE [CASRN 9002-88-4]



PRODUCT TECHNICAL PROPERTIES

Properties	Value	Unit	Testing Conditions	Test Method
Density	0.865 ± 0.03	g/cm ³	23 °C	ASTM D-792
Melt Flow Index	4.16 ± 0.3	g/10 min	190°C - 2.16 kg	ASTM D-1238
Ultimate Tensile Stress	5.49	MPa	50 mm/min	ASTM D-638
Elongation at Break	328.91	%	50 mm/min	ASTM D-638
Ash Content	≤ 10	%	60 min. - 700 °C	ASTM D-5630
Moisture Content	≤ 0.1	%	60 min. - 100 °C	ASTM D-6980

Recommended Application

This recycled Polyethylene grade is suitable for Polyethylene applications such as film, sheet, shopping bag, irrigation tube and electrical hose.etc..

PACKAGING

The default Package is 25 kg pack .
We could customize the package upon your request.

For more technical data sheets for other products , Feel free to
Contact Us





HAFEZ GROUP

Environmental Solutions



COMPANY PROFILE

2024-2025